Model	Go Go® Sport ¹
Part Number	3-wheel: \$73
Weight Capacity	325 lb / 147.4 kg
Maximum Speed ²	Up to 4.7 mph / 7.56 km/h
Ground Clearance ⁴	1.5" at motor / 0.75" at anti-tips
Turning Radius ⁴	3-wheel: 36" 4-wheel: 41.5"
Overall Length ⁴	3-wheel: 42" 4-wheel: 43"
Overall Width ⁴	21.25"
Seat-to-Ground Height	20.5" - 22"
Front Tires	3-wheel: 3" x 8" solid 4-wheel: 3" x 9" solid
Rear Tires	3" x 9" solid
Range Per Charge ^{1,2}	3-wheel: 12.75 mi / 20.51 km 4-wheel: 12 mi / 19.31 km
Total Weight With Batteries	3-wheel: 122.25 lb / 55.45 kg 4-wheel: 129.5 lb / 58.74 kg
Total Weight Without Batteries	3-wheel: 92.75 lb / 42 kg 4-wheel: 100 lb / 45.35 kg
Heaviest Piece When Disassembled (Front Section) ⁴	3-wheel: 35.75 lb / 16.22 kg 4-wheel: 44 lb / 19.96 kg
Standard Seating	Type: Compact, foldable Weight: 23 lb / 10.43 kg Material: Black vinyl Dimensions: Width: 17", Depth: 17"
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ⁵	(Two) 18 AH, 12 V, deep-cycle Weight: 14 lb / 6.35 kg each
Battery Charger	Off-board, 2 amp

- 1 Pride® FDA Class II Medical Devices are designed to aid individuals with
- 2 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a
- 3 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight
- 4 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 5 Battery weight may vary based on manufacturer.



pridemobility.ca | • • • • •



NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

CA_GOGOSPORT_Trifold_032825



TRAVEL READY, NOW WITH TIGHTER **TURNING!**

FEATURING EXCLUSIVE PATENTED





LIVE YOUR BEST®

pridemobility.ca | 🖸 f 🗴 🗑





NOW WITH TIGHTER TURNING!

FEATURING EXCLUSIVE PATENTED





4-wheel model shown; 3-wheel model available



Two sets of easily changeable, red and blue colored panels.

Feather-touch disassembly for quick transport or storage.

Exclusive EZ Turn Technology on 4-Wheel Model

The Go Go® Sport delivers high-performance and convenience on the go. With a 325 lb weight capacity, a charger port in the tiller, standard front LED lighting and a maximum speed up to 7.56 km/h, the Go Go Sport is feature rich and travel ready.

Additional Features

- Pride's exclusive EZ Turn technology (4W unit only) provides 3-wheel turning ability while maintaining 4-wheel stability
- Convenient dual charging port to charge batteries on and off unit
- Deck basket for additional storage (4-wheel only)
- Front frame-mounted seat post offers maximum stability
- Front tiller-mounted basket
- Long-lasting, high-intensity, front LED headlight offers optimal pathway illumination
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scuffing tires

Colors (both color panel sets included)



Accessories*

- Additional 18AH battery box
- Cane/crutch holder
- Cell phone holder
- Cup holder
- 50" Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror(s)
- Saddlebag

- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger
- Forearm crutch holder

Cup holder, rear basket, and saddlebag can be ordered as a bundle

^{*} Only one rear accessory can be used at a time.