





































			•														
	Go Go® iCRUISE®	i-Go™ 14	Go Go® Carbon ¹³	Go Go® Endurance Li ¹⁴	Go Go [®] Elite Traveller® 2	Go Go® Sport ¹⁴	Go Go® LX w/ CTS Suspension 14	Revo [®] 2.0 ¹⁴	PX4 ¹³	Pursuit 2 13	Pursuit XL ¹³	Zero Turn 10 13	Victory® LX 13	Pursuit ES 13	Victory® 10.2 14	Victory® Twin 13	Maxima ¹³
MODEL NUMBER	S25	SC20	SC25	S54LXLIT	SC442E	S73 (3-Wheel) S74 (4-Wheel)	S54LX	S67	SC134	SC7132	SC714	S710ZT	\$710LX	SC713CA SC713HS	S6102 (3-Wheel) S7102 (4-Wheel)	SC712	SC901 (3-Wheel) SC941 (4-Wheel)
WEIGHT CAPACITY	250 lb / 113.4 kg	275 lb / 124.7 kg	300 lb / 136 kg	325 lb / 147.4 kg	300 lb / 136 kg	325 lb / 147.4 kg	300 lb / 136 kg	400 lb / 181 kg	500 lb / 227 kg	350 lb / 158.7 kg	400 lb / 181 kg	400 lb / 181 kg	400 lb / 181 kg	350 lb / 158.7 kg	400 lb / 181 kg	350 lb / 158.7 kg	500 lb / 227 kg
SPEED (MAXIMUM) ²	3.7 mph / 6 km/h	4 mph / 6.4 km/h	3.7 mph / 6 km/h	4.1 mph / 6.6 km/h	4 mph / 6.4 km/h	4.7 mph / 7.6 km/h	4.4 mph / 7 km/h	5.2 mph 8.4 km/h	9.2 mph / 14.8 km/h	9.3 mph / 15 km/h	7.5 mph / 12 km/h	7.3 mph / 11.7 km/h	5.6 mph / 9 km/h	CA: 6 mph / 9.7 km/h HS: 9.5 mph / 15.3 km/h	5.2 mph / 8.4 km/h	5.7 mph / 9.2 km/h	5.8 mph / 9.3 km/h
GROUND CLEARANCE ⁴	1.3" at motor	4.2" at mid-frame	1.5" at motor	1.5" at motor 3.25" at side deck	1.34" at motor	1.5" at motor 3" at mid-frame	1.5" at motor	1.25" at transaxle 3.5" at mid-frame	3.5" at motor 4.4" at mid-frame	3.8" at transaxle	5.25" at rear frame	2" at motor 3" at mid frame	2.3" at motor 2.8" at front frame	3.5" at motor	2.5" at motor	2.25" at motor	SC901: 2.5" at motor 3" at mid-frame SC941: 2.25" at motor
3-WHEEL TURNING RADIUS 4	33.5"	45.9"	N/A	N/A	N/A	36"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	42"	42"	49"
4-WHEEL TURNING RADIUS 4	N/A	N/A	53"	48.25"	37"	50.5"	48"	52"	82.3"	69.3"	82"	43"	61.25"	68.5"	52.25"	N/A	53"
3-WHEEL LENGTH/WIDTH 4,10	38"/19.25"	44"/20.3"	N/A	N/A	N/A	42"/21.25"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45"/22.25"	46"/22.3"	47.5"/27"
4-WHEEL LENGTH/WIDTH 4,10	N/A	N/A	40.3"/17.5"	42"/20.5"	39.4"/19.5"	43"/21.25"	41.75"/20.5"	47"/20.75"	56"/27.8"	53.5"/25.60"	56.25"/27.25"	48"/24.25"	47" / 24"	53.5"/25"	47.25"/22.25"	N/A	47.5"/27"
FRONT TIRES 4	6.5" solid	8" solid (hub motor)	7" solid	8" solid	7" solid	S73: 8" solid S74: 9" solid	7" solid	9" solid or pneumatic	13" pneumatic	13" pneumatic	13" pneumatic	9" solid	10" solid or pneumatic	13" pneumatic (flat-free optional) ⁷	10" solid (pneumatic optional) ⁷	(2) 9" solid	SC901: 10.5" solid SC941: 10" solid
REAR TIRES ⁴	6.75" solid	9" perforated	8" solid	8" solid	8" solid	9" solid	8" solid	9" solid or pneumatic	13" pneumatic	13" pneumatic	13" pneumatic	10.75" solid	10" solid or pneumatic	13" pneumatic (flat-free optional) ⁷	10" solid (pneumatic optional) ⁷	10" solid	10.75" solid
SUSPENSION	N/A	N/A	N/A	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	N/A
RANGE PER CHARGE ^{2,8,12}	12 mi / 20 km (tested at 200 lb / 90.7 kg)	9.3 mi / 15 km (tested at 200 lb / 90.7 kg)	10 mi / 16 km	8 Ah: 6.6 mi / 10.6 km 16 Ah: 13.2 mi / 21.3 km (tested at 200 lb / 90.7 kg)		S73: 12.75 mi / 20.5 km S74: 12 mi / 19.3 km (tested at 325 lb / 147.4 kg)	10.5 mi / 17 km (tested at 300 lb / 136 kg)	17.8 mi / 28.6 km (tested at 200 lb / 90.7 kg)	23.4 mi / 37.7 km (tested at 220 lb / 99.8 kg)	D I D - + + 7.	75Ah: 22.13 mi / 35.6 km 100Ah: 29.5 mi / 47.5 km (tested at 400 lb / 181 kg)	Z1.Z1111/34.1 KIII			U1: 11mi / 18 km 40 Ah: \$6102 -13 mi / 21 km; \$7102 -13.5 mi / 21.5 km (tested at 400 lb / 181 kg)		SC901: 19.8 mi / 31.8 km SC941: 19.5 mi / 31.4 km (tested at 500 lb / 227 kg)
TOTAL WEIGHT WITHOUT BATTERIES 3.4.11	42 lb / 19 kg	60.6 lb / 27.5 kg	35 lb / 15.9 kg	93 lb / 42.2 kg	83 lb / 37.7 kg	S73: 92.8 lb / 42.1 kg S74: 100 lb / 45.4 kg	90 lb / 40.8 kg	132 lb / 60 kg	253.8 lb / 115.1 kg	220.6 lb / 100 kg	259.5 lb / 117.7 kg	181.8 lb / 82.5 kg	165.6 lb / 75 kg	161 lb / 73 kg	S6102: 130.25 lb / 59 kg S7102: 139 lb / 63 kg	150.5 lb / 68.3 kg	SC901: 183.5 lb / 83.3 kg SC941: 196.5 lb / 89.1 kg
WEIGHT OF HEAVIEST PIECE ⁴	32 lb / 14.5 kg (Scooter Base)	32.8 lb / 14.9 kg (Rear Section)	35 lb / 15.9 kg	40.8 lb / 18.5 kg (Front Section)	35 lb / 15.9 kg (Front Section)	S73: 35.8 lb / 16.2 kg (Front Section) S74: 44 lb / 20 kg (Front Section)	39 lb / 17.75 kg (Front Section)	57 lb / 26 kg (Front Section)	201.2 lb / 91.3 kg	166 lb / 75.3 kg	205.5 lb / 93.2 kg	75 lb / 34 kg (Front Section)	76.8 lb / 34.8 kg (Front Section)	118 lb / 53.5 kg	S6102: 56.5 lb / 25.6 kg S7102: 64.5 lb / 29.2 kg (Front Section)	55 lb / 25 kg (Front Section)	SC901: 135.25 lb/61.4 kg SC941: 143.5 lb/65.1 kg
STANDARD SEATING ⁴	Compact, Foldable (14.75" x 13.5")	Compact, Foldable with Removable Back (16" x 16")	Integrated, Fold-down Backrest, Removable Cushions (14" x 11.5")	(17" v 17")	Compact, Mesh, Foldable (17" x 17")	Compact, Foldable (17" x 17")	Compact, Foldable (17" x 17")	Compact, Foldable (20" x 18")	High Back (19.2 x 19.5 -21.3")	High Back (20" x 18")	High Back (18" x 18")	Compact, Foldable (18" x 17")	High Back (18"x18")	High Back (18" x 18")	Compact, Foldable (18" x 17")	Compact, Foldable (18" x 17")	High Back (22" x 18"-20")
BATTERY REQUIREMENTS	36V, 5.2Ah ⁶ Lithium-ion	25.2V, 9.6Ah ⁶ Lithium-ion	24V, 12Ah ⁶ Lithium-ion	8Ah: Lithium-ion ⁶ or 16Ah: Lithium-ion ⁷	(2) 18Ah ⁶ (SLA/AGM)	(2) 18Ah ⁶ (SLA/AGM)	(2) 18Ah ⁶ (SLA/AGM)	(2) U-1 ⁶ (SLA/AGM)	(2) 12V 75Ah ⁷ (SLA)	24V 50Ah ⁶ or Dual -24V 50Ah ⁷ Lithium-ion	(2) 12V 75Ah ⁷ or (2) 12V 100Ah ⁷ (SLA)	(2) 40Ah ⁶ (SLA/AGM)	(2) 40Ah ⁶ (SLA/AGM)	(2) 12V 75Ah ⁷ (SLA)	(2) U-1 ⁶ or (2) 40Ah ⁷ (SLA/AGM)	(2) U-1 ⁶ or (2) 40Ah ⁷ (SLA/AGM)	(2) GEL, 58Ah, NF-22 ⁶ (Nano-silica)
BATTERY WEIGHT?	4.5 lb / 2 kg ⁵	4.8 lb / 2.2 kg ⁵	4 lb / 1.8 kg ⁵	8 Ah: 8 lb / 3.6 kg ⁵ 16 Ah: 12 lb / 5.4 kg ⁵	29.6 lb / 13.4 kg ⁵	27.5 lb / 12.5 kg ⁵	30 lb / 14 kg ⁵	25 lb / 11.3 kg ⁵ ea.	48.8 lb / 22.2 kg ea.	23.8 lb / 10.8 kg ea.	75Ah: 55 lb / 25 kg ea 100Ah: 60.5 lb / 27.5 kg ea	30.3 lb / 13.8 kg	32 lb / 14.5 kg ea	53 lb / 24 kg ea.	U1: 22.5 lb 10.3 kg ea. 40Ah: 32.5 lb / 14.8 kg ea.		36.5 lb / 16.6 kg ea.
BATTERY CHARGER	Off-board, 36V (Lithium-ion)	Off-board, 3.5A (Lithium-ion)	Off-board, 2A (Lithium-ion)	Off-board, 3.5A (Lithium-ion)	Off-board, 2A	Off-board, 2A	Off-board, 2A	Off-board, 3.5A	Off-board, 8A	Off-board, 8A	Off-board, 8A	Off-board, 3.5A	Off-board, 5A	Off-board, 8A	Off-board, 3.5A	Off-board, 3.5A	Off-board, 5A
SEAT-TO-DECK HEIGHT RANGE ⁴	11.5" – 12.5"	14.6"	17"	16.25"-17.75"	16.4"-17.9"	17"-18"	16.25"-17.75"	16.5" - 18"	16.54"-18.39"	17.9"-20.9"	18"-19.5"	17.75"-19.25"	16.25" - 18.25"	17.75"-19.25"	17.5" – 18"	17.25"-18.75"	17.13" - 19.13"; or 17.36"-23.61" (with power elevating seat)
SEAT-TO-GROUND HEIGHT RANGE ⁴	19"-20"	22.25"	21.75"	21.25"-22.75"	21.5"-23"	20.5"-22"	20.75"-22.25"	22"-23.5"	24.17"-25.59"	24.75"-26.75"	26.25"-27.75"	23.25"-24.75"	23.5" - 25.5"	24.75"-26.25"	23.5"- 25"	23"-24.5"	22.1" - 24.1"; or 22.32"-28.57" (with power elevating seat)
STANDARD BASE COLORS	Gloss Colours: Lime, Mango, Arctic Ice, Blackberry, Raspberry	Matte Colours: Sugar Plum, Iceberg Blue, Black, White	Black Carbon Fiber	Garnet Red (Matte) & Euro Grey (Gloss) (Interchangeable shrouds)	Matte Colours: Black (Standard), Sugar Plum, Iceberg Blue, White, Robin's Egg Blue, Chell-o,Tangerine, Cardinal Red	Gloss Colours: Red & Blue (Interchangeable shrouds)	Gloss Clours: Red & Blue (Interchangeable shrouds)	Gloss Colours: Grey Street, True Blue	Accent Colours: Satin Aluminum, Red, Sunflower, Dark Violet, Peacock Blue	Gloss Colours: Black, Orange Matte Colours: Grey	Gloss Colours: Candy Apple Red, Silver	Gloss Clours: Candy Apple Red, Pearl White Matte Clours: Black, Ocean Blue	Gloss Colours: Candy Apple Red, Viper Blue	Gloss Colours: Candy Apple Red, Viper Blue	Gloss Candy Apple Red Matte Ocean Blue	Gloss Colours: Candy Apple Red, Viper Blue	Matte Colours: Garnet Red, Ocean Blue
WARRANTY	3-year limited on frame 2-year limited on electronics 1-year limited on Drivetrain, Motor, Battery, and Charger	3-year limited on Frame 2-year limited on Electronics 1-year limited on Drivetrain, Motor, Battery, and Charger	Lifetime limited on Frame; 1-year limited on Electronics 1-year limited on Drivetrain 1-year limited on Battery	Lifetime limited on Frame; 2-year limited on Electronics 2-year limited on Drivetrain 2-year limited on Battery	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime Limited on Frame; 2-year limited on Electronics; 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Battery	Lifetime Limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 3-year limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime Limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime Limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 13-month limited on Batteries
		TRAVEL MOBILITY							FULL-SIZE LUXURY			MID-SIZE LUXURY		VALUE SERIES			HEAVY-DUTY

FOOTNOTES

1. Pride® FDA Class II Medical Devices are designed to aid individuals with mobility

2. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.

3. Battery weight not included.

4. Due to manufacturing tolerances and continual product improvement, this specification

can be subject to variance of + or - 3%.

- Weight of battery and pack.
 Batteries included.
 Optional, up-charge may apply.
 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive
- system performance. Test conducted at maximum weight capacity.

 9. Battery weight may vary based on manufacturer.

- 10. Stowage width and length (not including seat).
- 11. Includes standard seat weight.
 12. See product specification sheet for additional details
- 13. Light package. 14. Pathway lighting.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or $-3\,\%$.



pridemobility.ca

